

WHAT IS CLAIMED IS:

1. (Currently Amended) A drive system comprising at least one vibrating motor having at least one vibration generator each as well as at least one resonator each and a device that is driven by the at least one motor, the resonator having a contact area that cooperates with a driven surface of the device to drive said device along a path with the path and driven surface extending along one of a straight or circular axis, at least one of the resonator contact area and the device surface having ~~at least one of a surface or a surface texture or~~ a surface profile configured to guide the device along the path by having side surfaces located on opposing sides of the path to keep the device between the side surfaces and on the path.
2. (Previously Presented) The drive system of Claim 1, wherein the vibrating generator is made of a piezoelectric material.
3. (Currently Amended) The drive system of Claim 2, wherein the contact area comprises an indentation or protrusion and the driven surface is of a different hardness and the contact area is shaped by wear.
4. (Currently Amended) The drive system of Claim 2, wherein the device surface driven by the contact area has a profile comprising ~~an indentation or protrusion~~ a protruding curved surface on an outer periphery of a rotating part with the side surfaces located on opposing sides of the protruding curved surface.
5. (Previously Presented) The drive system of Claim 2, wherein the device surface driven by the contact area has a profile comprising an indentation produced by wear.
6. (Currently Amended) The drive system of Claim 2, wherein the contact area on the resonator is made of a softer material than the driven surface~~further comprises regions with differing friction coefficients~~.
7. (Cancelled) The drive system of Claim 2, wherein the surface driven by the contact area surface comprises regions with differing friction coefficients.
8. (Cancelled) The drive system of Claim 2, wherein the surface driven by the contact area comprises a plurality of indentations or protrusions or several regions with differing friction coefficients, with each indentation, protrusion or region of differing friction coefficient being spaced apart in regular intervals with respect to each other.

9. (Cancelled) The drive system of Claim 2, wherein the surface driven by the contact area surface comprises comprising regions with differing friction coefficients.
10. (Currently Amended) The drive system of Claim 8, wherein the driven surface has a protruding curved cross-section and extends along at least a portion of a circular path~~indentations or the protrusions have a respective depth or height of about .05—10 mm.~~
11. (Currently Amended) The drive system of Claim 8, wherein the driven surface has a curved cross-section, and extends along a straight path~~indentations or the protrusions have a respective depth or height of about .5—3 mm.~~
12. (Previously Presented) The drive system of Claim 2 comprising at least two motors that are arranged in the same orientation to drive the driven element in the same direction.
13. (Previously Presented) The drive system of Claim 8, wherein the indentations or the protrusions have a respective depth or height of 0.5 – 3 mm.
14. (Previously Presented) The drive system of Claim 12, wherein the motors are urged against the driven device with respective forces that differ from each other.
15. (Previously Presented) The drive system of Claim 12, wherein the motors are controllable individually.
16. (Previously Presented) The drive system of Claim 12, wherein the motors are controllable in parallel.
17. (Previously Presented) The drive system of Claim 12, wherein the motors are operable at differing frequencies.
18. (Previously Presented) The drive system of Claim 12, wherein the motors each operate at differing amplitudes.
19. (Previously Presented) The drive system of Claim 12, wherein the motors move the driven device in two different directions.
20. (Previously Presented) The drive system of Claim 2, wherein the force of the generated motion is predetermined by the position of the driven device or the angle of the transducer relative to the driven device when the excitation to the motor remains the same.

21. (Previously Presented) A drive system comprising at least one vibrating motor having a vibration generator driving a resonator, the resonator having a contacting area engaging a driven surface of a driven element, one of the contacting area and driven surface having areas of different friction arranged to guide the driven element.
22. (Previously Presented) The drive system of Claim 21 wherein the driven surface comprises indentations or protrusions having a respective depth or height of about .05 – 10 mm.
23. (Previously Presented) The drive system of Claim 21 wherein one of the contacting surface and driven surface comprise regions with differing friction coefficients spaced apart at regular intervals.
24. (Previously Presented) The drive system of Claim 21 wherein the driven surface comprises indentations or protrusions spaced apart at regular intervals.
25. (Currently Amended) A drive system comprising at least one vibrating motor having a vibration generator driving a resonator, the resonator having a contacting area engaging a driven surface of a driven element to guide the driven element along one of a straight or circular path, one of the contacting area and driven surface being located on a protrusion located along sides of the path and extending into indentations formed in the other of the contacting area and driven surface an amount sufficient to guide the driven element relative to the resonator.
26. (Previously Presented) The drive system of Claim 25 wherein the driven surface comprises an indentation and the contacting surface comprises a protrusion with the protrusion having lateral sides contained within the indentation.
27. (Currently Amended) The drive system of Claim 25, wherein the driven surface comprises a protrusion having a cross-section with a curved surface at the driven surface and the contacting surface comprises an indentation.
28. (Currently Amended) The drive system of Claim 27, wherein the driven surface comprises ~~an indentation~~ a protrusion with a non-circular cross-section ~~and the contacting surface comprises a protrusions with the protrusion and being formed by curved.~~
29. (Previously Presented) The drive system of Claim 25 wherein one of the driven surface and the contacting surface comprises a surface with multiple curves forming

hills and valleys into which the protrusion is guided by contours of the multiple curves.

30. (New) A drive system comprising at least one vibrating motor having at least one vibration generator each as well as at least one resonator each and a device that is driven by the at least one motor, the resonator having a contact area that cooperates with a surface of the device to drive said device, at least one of the resonator contact area and the device surface having at least one of a surface texture or surface profile configured to guide the device, wherein the contact area on the resonator comprises regions with differing friction coefficients and wherein the generator is made of a piezoelectric material.
31. (New) A drive system comprising at least one vibrating motor having at least one vibration generator each as well as at least one resonator each and a device that is driven by the at least one motor, the resonator having a contact area that cooperates with a surface of the device to drive said device, at least one of the resonator contact area and the device surface having at least one of a surface texture or surface profile configured to guide the device, wherein the surface driven by the contact area surface comprises regions with differing friction coefficients and wherein the generator is made of a piezoelectric material.
32. (New) A drive system comprising at least one vibrating motor having at least one vibration generator each as well as at least one resonator each and a device that is driven by the at least one motor, the resonator having a contact area that cooperates with a surface of the device to drive said device, at least one of the resonator contact area and the device surface having at least one of a surface texture or surface profile configured to guide the device, wherein one of the surface driven by the contact area or the contact area comprise regions with differing friction coefficients.
33. (New) A drive system comprising at least one vibrating motor having a vibration generator driving a resonator, the resonator having a contacting area engaging a driven surface of a driven element to move the driven element along a path, one of the contacting area and driven surface having areas of different friction located on opposing sides of the path and engaged by the other of the contacting area and driven surface.

34. (New) The drive system of Claim 25 wherein the driven surface is of a harder material than the protrusion and the protrusion wears to conform to the shape of the driven surface.
35. (New) The drive system of Claim 25 wherein the resonator is of a softer material than the driven surface and selected to wears to conform to the shape of the driven surface.
36. (New) The drive system of Claim 25 wherein the path is straight and the contacting area has a cross section with a curved surface.
37. (New) The drive system of Claim 25 wherein the path is circular and the contacting area has a cross section with a curved surface and the driven surface is shaped to conform with the contacting surface.
38. (New) The drive system of Claim 25 wherein the resonator has a longitudinal axis which is in the same plane as the path.